

Variables for all objects on a map

Variable	Description	Type	Example
\$MAP_ID	ID of the map	integer	123
container_id	IDs of the containers in which the map is to be created	array	[1,2,3,...]
	Name of the icon set to be used	string	arrows_128px globe_64px ...
\$TYPE	The type of the included object	string	host hostgroup service servicegroup map
\$OBJECT_ID	ID of the included object	integer	\$HOST_ID \$HOSTGROUP_ID etc
x	Coordinate on the x-axis	integer	123
y	Coordinate on the y-axis	integer	123
Gadget specific			
gadget	Name of the gadget	string	Tacho TrafficLight Cylinder Text RRDGraph
transparent_background	If you want the gadget background to be transparent	integer	0 1 (default 0)
Mapline specific			
startX	Starting point on the X-axis	integer	123
endX	End point on the X axis	integer	123
startY	Starting point on the Y axis	integer	123
endY	End point on the Y axis	integer	123
Maptext specific			
text	Free text	string	Lorem ipsum dolor
<p>The following BB code can be used within the text field</p> <p>[color='#356E35'][/color] (Hexadecimal colour value) [text='small'][/text] (Options: xx-small x-small small large x-large xx-large) [b] [/b] [i] [/i] [u] [/u] [left] [/left] [center] [/center] [right] [/right] [justify] [/justify] [url='?' tab]Map link[/url] (url= Mapid, tab = open link in new tab) [url='https://www.google.de' tab]link description[/url] (url = url, tab = open link in new tab)</p>			